

# Electric Forklift Counterbalanced

Available with  
**LIION**



CPD10/15/18

Available with  
**LIION**



CPD20/25

Available with  
**LIION**



CPD30/35

Item		4 Wheels Pneumatics (2000-3500lbs)			4 Wheels Pneumatics (4000-5000lbs)		4 Wheels Pneumatics (6000-7000lbs)	
<b>Identification</b>								
Series		G series			G series		G series	
Model Designation		CPD10	CPD15	CPD18	CPD20	CPD25	CPD30	CPD35
Configuration Number		GD2			GD2		GD2	
Load Capacity	lbs	2000	3000	3500	4000	5000	6000	7000
Load Center	in	24	24	24	24	24	24	24
Operator Type		Seated			Seated		Seated	
<b>Dimensions</b>								
Overhead Guard Height	in	84	84	84	85	85	87	87,2
Overall Length (without fork)	in	81	81	81	90	90	98	101
Overall Width	in	43	43	43	47	47	49	48,9
Turning Radius (in standard battery compartment)	in	69	69	69	79	80	87	89,4
Right Stack Aisle Width (Pallet size 40x40in, clearance:7.9in)	in	131	131	131	143	144	153	156
Right Stack Aisle Width (Pallet size 47x47.2in, clearance:7.9in)	in	139	139	139	151	152	161	164
<b>Wheels, Chassis</b>								
Tire Type		Pneumatic			Pneumatic		Pneumatic	
<b>Weight</b>								
Total Approximate Weight (W/O battery)	lbs	6440/4940	6440/4940	7100/5360	9170/6750	9590/6950	10604/7627	12125/9149
<b>Performance</b>								
Travel Speed, Loaded/Unloaded	Km/h	15/15,9	15/15,10	15/15,11	14,5/15	14,5/16	15/15,5	14,5
Battery Voltage/rated capacity (5h)	V/Ah	48/480	48/480	48/480	48/700	48/700	80/480	80/560
Drive Motor - 60 min. rating	kW	8,2	8,3	8,4	11,5	11,6	16,9	16,1
Pump Motor - 15 min. rating	kW	10,6	10,7	10,8	15	16	13,2	13,3
Drive motor Control Method		MOSFET/AC			MOSFET/AC		MOSFET/AC	
Controls		ZAPI			ZAPI		ZAPI	

